

ASTM A135/A795

SUBMITTAL SHEET

ASTM A135/A795 fire protection sprinkler pipe is produced at our Nucor Tubular Products Trinity, Alabama division. Nucor is the industry's only 100% hydrotested pipe and is always made, melted, and rolled in the USA - so it's **steel you can trust**.

All Nucor ASTM A135/A795 fire protection sprinkler pipe has a black LED cured UV coating to ensure a clean, corrosion resistant surface. Additionally, all Nucor ASTM A135/A795 fire protection sprinkler pipe is coated in MIC guard, which is a water-based waxy emulsion corrosion inhibitor and biostatic MIC preventative for steel alone or in the presence of CPVC. Nucor MIC Guard is present in the coolant with concentration levels of 1-5%.

All Nucor ASTM A135/A795 fire protection sprinkler pipe is:

- UL & C-UL listed
- FM approved (1-8")
- EAF melted and manufactured in the USA
- ERW welded
- NDT weld tested (2" & above)
- Hydrotested (Working pressure rating 300psi)

Additional information:


- Standard lengths available in 21' and 42'
- Custom lengths (inquire for availability)
- Plain end (beveled) or roll grooved
- Black LED cured UV coating or bare
- Complies with NFPA 13 and 14
- NYC SCA approved

A135/A795 HYDROFLOW™

NPS	NOM OD	NOM ID	NOM Wall	Weight per Foot	PCS/BDL	CRR
1.25"	1.660"	1.520"	0.070"	1.19	61	1.71
1.5"	1.900"	1.750"	0.075"	1.46	61	1.65
2"	2.375"	2.207"	0.084"	2.06	37	1.93
2.5"	2.875"	2.703"	0.086"	2.56	30	1.19
3"	3.500"	3.314"	0.093"	3.39	19	1.08
4"	4.500"	4.304"	0.098"	4.61	19	0.81

A135/A795 TYPE E - SCHEDULE 10

NPS	NOM OD	NOM ID	NOM Wall	Weight per Foot	PCS/BDL
1.25"	1.660"	1.442"	0.109"	1.81	61
1.5"	1.900"	1.682"	0.109"	2.09	61
2"	2.375"	2.157"	0.109"	2.64	37
2.5"	2.875"	2.635"	0.120"	3.53	30
3"	3.500"	3.260"	0.120"	4.34	19
4"	4.500"	4.260"	0.120"	5.62	19
6"	6.625"	6.357"	0.134"	9.30	10
8"	8.625"	8.249"	0.188"	16.96	7



Submittal Information

Project:

Contractor:

Date:

Engineer:

Specification Reference:

System Type:

Locations:

Comments:
